

ALSCO® DURATEX™ HIGH PERFORMANCE, QUALITY TRIM COIL



MAINTAINS ITS HIGH QUALITY FINISH THROUGH FORMING, INSTALLATION. AND HARSH WEATHER

DESIGNED TO PROVIDE OPTIMUM UV PROTECTION, PREVENTING FADING FROM ULTRA-VIOLET RAYS FROM THE SUN

EASY CLEANING AND MAINTENANCE

LIFETIME LIMITED WARRANTY

ALSCO DuraTex™ trim coil is made to outperform other trim coils in every application. The DuraTex difference is found in its coating technology which is engineered to industry-leading standards. The low gloss, brushed surface texture of DuraTex trim coil enchances the craftsmanship that goes into the forming and installation of custom building components and withstands the harsh effects of the sun. And, now, DuraTex is available in 24 colors to complement any project. (See Reverse Side for Colors)

ALSCO® ALUMINUM DURATEX™ TRIM COIL SPECIFICATIONS

Material

All ALSCO Trim Coil shall be made of an ALSCO 3105-type aluminum sheet with a minimum tensile strength of 29,000 psi, or equivalent, as referenced in AAMA specification 1482-86 (paragraph 3.2.3). The metal shall be treated on both sides with a chemical conversion coating to ensure excellent paint adhesion and resistance to corrosion. ALSCO DuraTex[™] Trim Coil is coated on both sides with a high performance, roll-applied, mar-resistant, low-gloss textured polyester. The top surface is available in 24 colors and the reverse side is coated with G23 DuraTex White. All coatings conform to the standard commercial coatings specifications, as referenced in AAMA specification 1482-86 (paragraph 3.2.4).

ALSCO DuraTex trim coil is packaged with one roll per carton. All 24" coils shall be packaged with 32 rolls per skid. Coil shall be of the following width, length and thickness:

ProductWidthLength/RollNominal Thickness*CTP2424"50 feet.019"

Applications

DuraTex tough low gloss, lightly textured finish makes it the perfect choice for demanding applications.

ALSCO DuraTex Aluminum Trim Coil is designed for residential and light commercial applications. Trim coil can be field-formed to provide low-maintenance coverings for exterior trim surfaces such as window and door casings, window sills, drip caps, fascias, porch posts, louvers, flashings, etc. Trim sheet shall be attached with color-matched stainless steel or aluminum painted trim nails.

Application Considerations

Direct contact of aluminum product(s) with certain dissimilar materials or contact with the water run-off from such materials is likely to result in corrosion, which is not covered by the product warranty. Therefore, care should be exercised to avoid contact of aluminum with any corrosive materials during installation including, but not limited to: pretreated lumber, concrete, masonry cement, stucco, salt, corrosive chemicals, dissimilar metals (copper, zinc, steel, etc.), and roofing systems made with metallic granules of such dissimilar metals.

G23 DuraTex White	G030 - 30 Degree White	G034 Linen
G037 Brandywine	G049 Champagne	G050 Beige
G051 Cream	G052 Wheat	G054 Tan
G058 Sand	G062 Vintage Sage	G067 Jefferson Tan
G200 Black	G253 Bronze	G280 White
G362 Monterey Taupe	G522 Russet	G627 Granite Gray
G628 Tumbleweed Tan	G714 Sierra/Clay	GTAD Almond
GTHO Hickory Oak	GTMK Musket	GTSA Sandstone

Customer Service 1-800-521-2930 Fax: 1-800-348-2629

ALSCO

319 Logan St. Circleville, Ohio 43113

