



ALSCO® RAIN CARRYING PRODUCTS

GUTTER COIL AND ACCESSORIES SPECIFICATIONS



PROPER RAIN CARRYING PRODUCTS CAN PREVENT
WATER AND ICE DAMAGE AND EXTEND THE LIFE OF ROOF

BACKED BY ALSCO'S LIFETIME LIMITED WARRANTY

WIDE VARIETY OF GUTTER ACCESSORIES AVAILABLE TO
COMPLETE ALMOST EVERY INSTALLATION REQUIREMENT

ALSCO® rainware and gutter coil features Gutter Tuff®, a proprietary coating formulated to meet the unique and rigorous demands of field formed continuous gutter applications. In a carefully controlled laboratory test that simulated the most rigorous conditions under which field formed gutters are formed, Gutter Tuff outperformed other gutter coatings, hands down. Gutter Tuff is resistant to scuffing, metal marking, abrasion and is forgiving in misaligned roll formers.

ALSCO®

RAIN CARRYING PRODUCT SPECIFICATIONS

Material

- ALSCO gutter coil shall be made from a 3105-type alloy aluminum with a minimum tensile strength of 24,000 psi.
- ALSCO rain carrying system products are designed for use in residential and light commercial applications.
- ALSCO gutter coil shall be made available in two thicknesses: nominal 0.027" and nominal 0.032". The coil is available in widths that can be used to produce both 5-inch and 6-inch K-style gutters on all popular forming equipment. The standard thickness tolerance for products made from aluminum sheet material shall be +0.000", -0.003".
- ALSCO standard 2"x 3" and 3"x 4" downspout and type A and B elbows shall be available in nominal 0.019" thickness. Heavy Duty 3"x 4" downspouts in nominal 0.024" thickness shall also be available.
- Other gutter accessories shall be readily available including inside and outside box and strip miters, left and right end caps, hangers, drop outlets and fasteners.
- Prior to factory painting, the metal shall receive a special cleaning process to assure maximum paint adhesion. The inside of all gutters, downspouts and elbows shall be coated with a special corrosion inhibiting pretreatment and a protective polyester coating. The exteriors will be coated in a two-phase operation that includes a corrosion-inhibiting pretreatment and ALSCO's high performance Gutter-Tuff® coating system, designed specifically for on-site forming of seamless gutters.
- All accessories used with ALSCO rain carrying system products shall be ALSCO accessories designed for use with ALSCO materials, and shall have the same Gutter-Tuff coating to ensure that the warranty covering the rain carrying products and accessories is applicable to both.

CERTIFICATE OF CONFORMANCE

ALSCO gutters, downspouts and accessories shall meet or exceed the following specifications:

- Architectural Aluminum Manufacturers Association (AAMA) Specification 1405.1: Specifications for Aluminum Gutters and Downspouts.
- HUD Minimum Property Standard 4900.1 for One and Two Family Dwellings.
- HUD Minimum Property Standard 4910.1 For Multi-Family Dwellings.

Customer Service 1-800-521-2930

Fax: 1-800-348-2629

ALSCO

319 Logan St.
Circleville, Ohio 43113

www.alscometals.com

**ALSCO®**
Building Products Since 1947